

# 4762

## High Precision Current Comparator 400A

*Datasheet*



Sold & Serviced in USA by:



HV TECHNOLOGIES, Inc.

8526 Virginia Meadows Dr.

Manassas, VA 20109

(703) 365-2330

[www.hvtechnologies.com](http://www.hvtechnologies.com)

[hvsales@hvtechnologies.com](mailto:hvsales@hvtechnologies.com)



Current and voltage – our passion

Designed by



# General Description

The high precision Current Comparators (current transformers) are used to convert high currents to a lower, measureable level.

The errors of conventional standard current transformers inevitably depend on their burden. A magnetic flux in the core produces the e.m.f. which sustains the secondary current in the burden.

This disadvantage has been eliminated by the development of the new current comparators.

An indicator winding measures the magnetic flux in the core, while an amplifier - by regulating the current in a compensating winding - ensures that the amplitude of the residual flux in the core is approximately zero.

With this technique, the high precision Current Comparators will maintain typical current ratio errors below 20 ppm and current phase errors below 0.15 min on a long term basis over an extremely broad current range.

This electronically controlled current transformer is specifically designed for current range extension in capacitance measurements. It has divider measurements of 1:10 and 1:100.

The special transformer is accommodated inside a portable casing with all terminals on the top panel.

## Features

- Especially suitable for range extension of capacitance and  $\tan \delta$  measuring bridges
- Outstanding accuracy and stability over a very broad working range 10mA ... 400A

## Advantages

- ☑ Negligible transformer error eliminates calculation of measured C and  $\tan \delta$  correction factors
- ☑ **Accuracy at best level** – The 4762 units are prepared for accuracy testing of current instrument transformers with most stringent accuracy requirements – 476x units are qualified for use as standard current transformers in metrology institutes.

# Applications

- Accuracy test on current instrument transformers
- Range extension of capacitance and  $\tan \delta$  bridges

## Scope of Supply

- Current Comparator 4762 (115 or 230V type -> specify in order),
- Mains cable

## Technical Data

Accuracy Specification		
Current Ratio	1 : 10	1 : 100
min. primary current	10 mA	100 mA
max. primary current	40 A	400 A
min. secondary current	1 mA	1 mA
max. secondary current	4 A	4 A
Burden	Max. 1 $\Omega$	
Current error	< 0.002 %	
Phase angle @ burden < 0.1 $\Omega$	< 0.05 min or < $1.5 \times 10^{-5}$ radian ( $\tan \delta$ )	
Phase angle @ burden < 1 $\Omega$	< 0.15 min or < $4 \times 10^{-5}$ radian ( $\tan \delta$ )	
Frequency Range	45 to 65 Hz	
Mechanical and Power Supply		
Dimensions (W x D x H)	305 x 180 x 255 mm (12 x 7.1 x 10")	
Weight	9.5 kg (20.9 lbs)	
Power supply Spec.	230 or 115 VAC, 50/60 Hz	

Sold & Serviced in USA by:



HV TECHNOLOGIES, Inc.

8526 Virginia Meadows Dr.  
Manassas, VA 20109  
(703) 365-2330  
[www.hvtechnologies.com](http://www.hvtechnologies.com)  
[hvsales@hvtechnologies.com](mailto:hvsales@hvtechnologies.com)

## Global Presence

### Europe

HAEFELY AG  
Birsstrasse 300  
4052 Basel  
Switzerland

☎ + 41 61 373 4111  
✉ [sales@haefely.com](mailto:sales@haefely.com)

### China

HAEFELY AG Representative Office  
8-1-602, Fortune Street, No. 67  
Chaoyang Road, Beijing 100025  
China

☎ + 86 10 8578 8099  
✉ [sales@haefely.com.cn](mailto:sales@haefely.com.cn)

This document has been drawn up with the utmost care. We cannot, however, guarantee that it is entirely complete, correct or up to date.  
©Copyright HAEFELY/ Subject to change without notice

V20XX.XX



**HAEFELY**

Current and voltage – our passion



HIGH VOLTAGE



INSTRUMENTS



EMC

  
precision.  
**swiss made.**