

IDAS 2823

High Precision $\tan \delta$ / Power factor Measuring Instrument

Datasheet



Sold & Serviced in USA by:



HV TECHNOLOGIES, Inc.

8526 Virginia Meadows Dr.

Manassas, VA 20109

(703) 365-2330

www.hvtechnologies.com

hvsales@hvtechnologies.com



HAEFELY

Current and voltage – our passion

Designed by



General Description

The IDAS 2823 High Precision tan d / power factor measuring instrument is designed for measurement of very low dielectric losses of high-voltage apparatus.

The IDAS 2823 belongs to our new generation of measuring instruments, and is a perfect combination of over 50 years' experience in this field and state-of-the-art technologies.

The use of an optically decoupled connection allows complete galvanic isolation between control room and test field and guarantees highest safety level of test personnel.

It is capable of analyzing capacitive and inductive loads with outstanding accuracy and stability..

Features	Advantages
<ul style="list-style-type: none">▪ Compact, reliable and EMC hardened design, IP50	<ul style="list-style-type: none">☑ The galvanic isolation ensures fully safety of the personnel. With the 2823, there is no electrical connection between the control room and the high voltage test room.
<ul style="list-style-type: none">▪ Optically decoupled from computer	<ul style="list-style-type: none">☑ Simple connection to test objects without external shunts or hardware reconnection due to the high input current range.
<ul style="list-style-type: none">▪ Up to 15A input current with auto-range	<ul style="list-style-type: none">☑ Increased linearity and extended frequency measuring range up to 1 kHz.
<ul style="list-style-type: none">▪ Extremely low input impedance	<ul style="list-style-type: none">☑ Backward compatible with older instruments and cabling, same connectors used for over 40 years.
<ul style="list-style-type: none">▪ Industrial connectors for measuring and fiber optic connectors	<ul style="list-style-type: none">☑ Turnkey solution from one supplier possible (including power supplies, standard capacitors, current comparators, test cells, certified calibration).
<ul style="list-style-type: none">▪ Mains Powered	<ul style="list-style-type: none">☑ Connect and forget, no battery pack or recharge needed.

Applications

Routine and type tests of:

- Power Cables & Accessories
- Capacitors
- Instrument Transformers
- Bushings & Isolators
- Research & Development

Technical Data

Measurement	Range	Max. Resolution	Accuracy
Dissipation Factor ($\tan \delta$) ⁽¹⁾	0 ... 100	1 x10 ⁻⁵	± 0.1 % RD ± 5 x 10 ⁻⁵
Power Factor ($\cos \varphi$) ⁽¹⁾	0 ... 1	1 x10 ⁻⁵	± 0.1 % RD ± 5 x 10 ⁻⁵
Capacitance ⁽²⁾	≥ 0.1 pF	0.01 pF	± 0.1 % RD ± 0.05 pF
Inductance ⁽²⁾	≤ 1000 kH	0.1 mH	± 0.2 % RD ± 0.3 mH
Test voltage	> 5 V	1 V	± 0.2 % RD ± 1 V
Test Current @ Input Cn ⁽²⁾	10 µA ... 300 mA	1 nA	± 0.1 % RD ± 0.1 nA
Test Current @ Input Cx ⁽²⁾	10 µA ... 15 A	1 nA	± 0.1 % RD ± 0.1 nA
Test Frequency	15 ... 1000 Hz	0.01 Hz	± 0.1 % RD ± 0.02 Hz
Apparent Power S ⁽²⁾	≥ 1 mVA	0.1 mVA	± 0.5 % RD ± 1 mVA
Real Power P ⁽²⁾	≥ 1 mW	0.1 mW	± 0.5 % RD ± 1 mW
Reactive Power Q ⁽²⁾	≥ 1 mVAr	0.1 mVAr	± 0.5 % RD ± 1 mVAr

⁽¹⁾ valid for temperature 5 .. 45 °C

⁽²⁾ valid for reference conditions 23°C ±5 °C

Hardware

Measuring channels	2 (C _N & C _X)
Link 2823 to Media Box	Fiber optic cable with rugged HARTING connectors, Han3A-gw-M20, SC type, IP44
Link Media Box to Controller	USB 2.0
Controller	External computer (not included)

Software

Controller requirements	Intel Core i3® / AMD Athlon II X2® or better. 1 GB RAM, Microsoft Windows 7 or 10 1 x USB 2.0 port free
Measuring time	0.3 s / measurement
Data format	XML & CSV
Recorded values	DF ($\tan \delta$), DF ($\tan \delta$)@20 °C, DF($\tan \delta$)[%], DF ($\tan \delta$)[%]@20 °C, PF ($\cos \varphi$), PF ($\cos \varphi$)@20 °C, PF ($\cos \varphi$)[%], PF ($\cos \varphi$)[%]@20 °C, QF (quality factor), QF (quality factor)@20 °C, C _P (Z _X = C _P R _P), R _P (Z _X = C _P R _P), C _S (Z _X = C _S + R _S), R _S (Z _X = C _S + R _S), C _n (Standard Capacitor Value), L _S (Z _X = L _S + R _S), R _S (Z _X = L _S + R _S), L _P (Z _X = L _P R _P), R _P (Z _X = L _P R _P), U _{RMS} , U _{RMS} /√3, U _{peak} /√2, I _{X RMS} , I _{N RMS} , I _m , I _{fe} , Impedance Z _x , Phase-angle φ (Z _X), Admittance Y _x , Frequency _{Test} , Apparent Power S, Real Power P, Reactive Power Q, Real Power@2.5 kV, Real Power@10 kV

Environmental Mechanical and Power Supply

Operating temperature	0 °C ... +55 °C
Storage temperature	-20 °C ... +70 °C
Humidity	5 ... 90 % r.h., non-condensing
Dimensions (W x D x H)	345 x 360 x 130 mm (13.6 x 14.2 x 5.2 in)
Weight	7.2 kg (15.9 lb)
Power supply Spec.	90 ... 264 V AC, 50/60 Hz, 50VA

PC, Screen Resolution and Operation System Requirements

PC min. configuration	Intel Core i3® / AMD Athlon II X2® or better, 1 GB RAM, Ethernet / USB 2.0
Screen resolution	1280 x 800 (WXGA)
Operation system	Windows 7™, or Windows 10™

Applicable Standards

Protection Class	IP 50
CE conformity	EMC Directive 2014/30/EU and RoHS Directive 2011/65/EU
Vibration Tests	IEC 60068-2-64 Spec A1 Transportation a1

Sold & Serviced in USA by:



HV TECHNOLOGIES, Inc.

8526 Virginia Meadows Dr.
Manassas, VA 20109
(703) 365-2330
www.hvtechnologies.com
hvsales@hvtechnologies.com

Global Presence

Europe

HAEFELY AG
Birsstrasse 300
4052 Basel
Switzerland

☎ + 41 61 373 4111
✉ sales@haefely.com

China

HAEFELY AG Representative Office
8-1-602, Fortune Street, No. 67
Chaoyang Road, Beijing 100025
China

☎ + 86 10 8578 8099
✉ sales@haefely.com.cn

This document has been drawn up with the utmost care. We cannot, however, guarantee that it is entirely complete, correct or up to date.
©Copyright HAEFELY/ Subject to change without notice

V2020.04



HAEFELY

Current and voltage – our passion



H HIGH VOLTAGE

I INSTRUMENTS

E EMC

precision. 
swiss made.